

Maryland Shallow Water Monitoring Program – 2014 Continuous Monitoring

Metadata:

Identification_Information:

Citation:

Citation_Information:

Originator: Maryland Department of Natural Resources, Resource Assessment Service (MD DNR RAS)

Publication_Date: 20150424

Title: MD DNR Continuous Water Quality Monitoring Project 2014

Geospatial_Data_Presentation_Form: Spatial dataset

Description:

Abstract:

Water quality was monitored at thirty-two Maryland shallow water sites located in Chesapeake Bay, Chesapeake Bay tributaries and Maryland Coastal Bay tributaries during 2014. YSI (6600 V2 or EXO2) data loggers sampled seven environmental parameters: water temperature, specific conductance, dissolved oxygen concentration, oxygen percent saturation, pH, turbidity and fluorescence. Water depth was measured at stations where loggers were deployed at fixed depths. Salinity and chlorophyll were derived from specific conductance and fluorescence, respectively. Each parameter was sampled at 15-minute intervals, except at stations XEF3551 and XFG4618. The surface and bottom monitors at station XEF3551 and the monitor at station XFG4618 sampled parameters at 60-minute intervals for the entire deployment. The number of days that data were collected at individual stations ranged from ninety to three hundred sixty-five.

Data loggers at most stations were exchanged bi-weekly. Data Loggers deployed from November through March were exchanged monthly because less biofouling, which may compromise data integrity, occurs during cold weather months. Data loggers deployed greater than 10m below surface at station XEF3551 were exchanged monthly. Data loggers deployed in a contained lake at station MZC0016 were exchanged monthly. Loggers were deployed simultaneously at two depths at stations XEF3551 and XHH4931.

When data loggers were exchanged, water samples for pigments, nutrients and suspended solids were collected for later analysis. At the same time, Secchi disk depth was measured and a Hydrolab (series IVa or V) water quality sonde was used to collect discrete water temperature, salinity, dissolved oxygen and pH data. Light attenuation was also measured using a LiCor instrument.

Purpose:

The Maryland Department of Natural Resources Shallow Water Monitoring program is part of a cooperative effort between the Federal government and State and local governments in the

Chesapeake Bay watershed to assess the ambient water quality criteria for dissolved oxygen, chlorophyll and water clarity in shallow water habitats. The Shallow Water Monitoring Program includes two components, the Water Quality Mapping Project and the Continuous Water Quality Monitoring Project.

Continuous Water Quality monitoring data describe the 2014 state of thirty-two shallow water sites on Chesapeake Bay and Maryland Coastal Bay tributaries using key water quality indicators.

The information is integrated with data from other Bay water quality stations and living resources monitoring projects and used to understand linkages, temporal variation and long-term trends.

Water quality data are used to refine, calibrate and validate Chesapeake Bay ecological models. The models are used to develop and assess water quality criteria with the goal of removing the Chesapeake Bay and its tidal rivers from the list of impaired waters.

Supplemental Information:

The target audiences for this information include Resource Managers, Technical/Scientific Users, Government, Educators, Students and General Public.

Data users who desire very detailed information about Water Quality Monitoring data-definition, sampling-procedures and data-processing are encouraged to refer to the documents listed below.

Water Quality Database - Database Design and Data Dictionary Prepared For: U.S. Environmental Protection Agency, Region III, Chesapeake Bay Program Office, January 2004. [http://www.chesapeakebay.net/documents/3676/cbwqdb2004_rb.pdf]

The most current version of the Water Quality Data Dictionary - Online may be found at: [http://archive.chesapeakebay.net/data/data_dict.cfm?DB_CODE=CBP_WQDB]

Guide to Using Chesapeake Bay Program Water Quality Monitoring Data, EPA 903-R-12-001, February 2012, CBP/TRS 304-12 [http://www.chesapeakebay.net/documents/3676/wq_data_userguide_10feb12_mod.pdf]

Quality Assurance Project Plan for the Maryland Department of Natural Resources, Chesapeake Bay Shallow Water Quality Monitoring Program, for the period July 1, 2014 - June 30, 2015. [http://mddnr.chesapeakebay.net/eyesonthebay/documents/SWM_QAPP_2014_2015_Draft_v3.pdf]

Time_Period_of_Content:

Time_Period_Information:

Range_of_Dates/Times:

Beginning_Date: 20140101

Ending_Date: 20141231

Currentness_Reference: Ground condition

Status:

Progress: Complete

Maintenance_and_Update_Frequency: As needed

Spatial_Domain:

Bounding_Coordinates:

West_Bounding_Coordinate: -79.4938

East_Bounding_Coordinate: -75.0405

North_Bounding_Coordinate: 39.7425

South_Bounding_Coordinate: 37.8713

Keywords:

Theme:

Theme_Keyword_Thesaurus:

Global Change Master Directory (GCMD), 2015. GCMD Keywords, Version 8.1. Greenbelt, MD: Global Change Data Center, Science and Exploration Directorate, Goddard Space Flight Center (GSFC) National Aeronautics and Space Administration (NASA).

online: [<http://gcmd.nasa.gov/learn/keywords.html>]

Theme_Keyword: Biosphere > Aquatic Ecosystems > Estuarine Habitat

Theme_Keyword: Biosphere > Aquatic Ecosystems > Rivers/Stream Habitat

Theme_Keyword: Biosphere > Ecological Dynamics > Ecosystem Functions > Nutrient

Cycling

Theme_Keyword: Biosphere > Ecological Dynamics > Ecosystem Functions > Primary

Production

Theme_Keyword: Terrestrial Hydrosphere > Surface Water > Rivers/Streams

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry > Chlorophyll

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry >

Conductivity

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry > Light

Transmission

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry > Nitrogen

Compounds

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry > Oxygen

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry > Nutrients

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry > pH

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry >

Phosphorous Compounds

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry > Suspended

Solids

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry > Turbidity

Theme_Keyword: Terrestrial Hydrosphere > Water Quality/Water Chemistry > Water

Temperature

Place:

Place_Keyword_Thesaurus: Producer Defined

Place_Keyword: United States

Place_Keyword: Maryland
Place_Keyword: Chesapeake Bay Watershed
Place_Keyword: Chesapeake Bay
Place_Keyword: Anne Arundel County
Place_Keyword: Baltimore City
Place_Keyword: Baltimore County
Place_Keyword: Calvert County
Place_Keyword: Caroline County
Place_Keyword: Cecil County
Place_Keyword: Charles County
Place_Keyword: Dorchester County
Place_Keyword: Harford County
Place_Keyword: Kent County
Place_Keyword: Prince George's County
Place_Keyword: Queen Anne's County
Place_Keyword: Somerset County
Place_Keyword: St. Mary's County
Place_Keyword: Talbot County
Place_Keyword: Wicomico County
Place_Keyword: Worcester County
Place_Keyword: Assawoman Bay
Place_Keyword: Back River
Place_Keyword: Bush River
Place_Keyword: Chincoteague Bay
Place_Keyword: Choptank River
Place_Keyword: Coastal Bays
Place_Keyword: Corsica River
Place_Keyword: Harris Creek
Place_Keyword: Mattawoman Creek
Place_Keyword: Nanticoke River
Place_Keyword: Patapsco River
Place_Keyword: Patuxent River
Place_Keyword: Pocomoke River
Place_Keyword: Potomac River
Place_Keyword: Sassafra River
Place_Keyword: Susquehanna Flats
Place_Keyword: Susquehanna River
Place_Keyword: Wicomico River
Place_Keyword: Williston Lake

Temporal:

Temporal_Keyword_Thesaurus: None

Temporal_Keyword: 2014

Access_Constraints: None

Use_Constraints: Acknowledgement of the MD Department of Natural Resources, Resource Assessment Service as a data source would be appreciated in products developed from these

data. Please use the following citation: Maryland Department of Natural Resources, Resource Assessment Service. Eyes on the Bay. URL: [<http://www.eyesonthebay.net>].

Point_of_Contact:

Contact_Information:

Contact_Person_Primary:

Contact_Person: Mark Trice

Contact_Position: Chief, Water Quality Informatics

Contact_Address:

Address_Type: Mailing Address

Address: MDDNR, 580 Taylor Avenue, D2

City: Annapolis

State_or_Province: MD

Postal_Code: 21401

Contact_Voice_Telephone: 410 260-8630

Contact_Electronic_Mail_Address: Mark.Trice_nospam_@maryland.gov[Remove_nospam_ for valid email address]

Browse_Graphic:

Browse_Graphic_File_Name:

[http://mddnr.chesapeakebay.net/newmontech/contmon/stn_map/Cmon_stns_2014.pdf]

Browse_Graphic_File_Description:

Map of thirty-two 2014 Continuous Monitoring Sites.

Browse_Graphic_File_Type: PDF

Data_Set_Credit:

Maryland Department of Natural Resources (MDDNR) Resource Assessment Service (RAS) staff collected the majority of samples and processed the data. The Nutrient Analytical Services Laboratory (NASL) at the Chesapeake Biological Laboratory (Univ. of MD) analyzed the nutrient, chlorophyll and suspended solids samples.

The project was made possible with funding provided by The State of Maryland, the United States Environmental Protection Agency Chesapeake Bay Program, the National Atmospheric and Oceanic Administration Chesapeake Bay Office and National Estuarine Research Reserve System program, and the Dominion Foundation.

Data_Quality_Information:

Attribute_Accuracy:

Attribute_Accuracy_Report:

Quality Assurance/Quality Control: MD DNR followed specific procedures to ensure that the Shallow Water Quality Monitoring Program project design was properly implemented and managed with sufficient accuracy, precision and detection limits. Accuracy (closeness to the true value) of collected data was controlled and assured by the proper use, calibration and maintenance of both field and laboratory equipment for the measurement of physical and chemical parameters.

The YSI 6600 V2 sondes were configured with the following probes: 6560(conductivity/temperature); 6561(flat glass pH) or 6579(tall pH); 6136(turbidity);

6150(ROX dissolved oxygen); 6025(fluorescence/chlorophyll). Sondes at one site (XHH3851) were also configured with 6132 (blue-green phycoerythrin) probes and sondes at two additional sites (XEA3687 and XJI2396) were also configured with 6131 (blue-green phycocyanin) probes.

The YSI EXO2 sondes were configured with the following probes: 599870-01(conductivity/temperature); 599702(unguarded pH); 599101-01(turbidity); 599100-01(optical dissolved oxygen); 599103-01(total algal chlorophyll and phycoerythrin).

Resolution, range and accuracy specifications for the sonde and probes may be obtained from the manufacturer. [<http://www.yisi.com/support.php>]

Procedures used to control and assure the accuracy of field measurements consisted of calibration of field instruments, verification of calibrations, equipment maintenance, and collection of filter blanks. Details of how data acquired with YSI sondes were quality assured and quality controlled may be found in the process description elements in the Lineage portion of this metadata record.

Water quality laboratory analysis results were used to calibrate and cross-check sonde data for accuracy. Daily quality control checks (including the running of blanks and standards) were used to control and assure laboratory accuracy.

Accuracy of Chesapeake Biological Laboratory, Nutrient Analytical Services Laboratory (CBL NASL) laboratory results was also assessed through DNR's participation in the Chesapeake Bay Coordinated Split Sample Program (CSSP), a split sampling program in which five laboratories involved in Chesapeake Bay monitoring analyze the coordinated split samples. CSSP was established in June 1989 to establish a measure of comparability between sampling and analytical operations for water quality monitoring throughout the Chesapeake Bay and its tributaries. DNR followed the protocols in the Chesapeake Bay Coordinated Split Sample Program Implementation Guidelines (EPA 1991) and its revisions. Split samples were collected quarterly. Results were analyzed by appropriate statistical methods to determine if results differed significantly among labs. If a difference occurred, discussions began regarding techniques and potential method changes to resolve discrepancies.

Additionally, CBL NASL participated two times per year in the United States Geologic Survey (USGS) reference sample program.

Logical Consistency Report:

Two of the attributes in the water quality data set are PARAMETER and VALUE. In cases where PARAMETER value is "SIGMA_T" and the VALUE measurement in the record is a negative number, the number should be considered unreliable. SIGMA_T values are not measured. SIGMA_T values are derived.

During 2014, at all but two stations, water quality monitoring sondes were deployed at a single depth. At two stations: Possum Point (XHH4931) and the Gooses (XEF3551) sondes

were deployed concurrently at two depths: one meter from the surface and 0.3 meters from the bottom.

Values in the 'LAYER' column of sonde data files may be used to determine the depth at which a sonde was deployed. Sonde data from all 2014 sites, except XHH4931, XEF3551, and XFG4618 list a value of 'BS', 'below surface' in the LAYER column. Stations with a LAYER value of 'BS' will have varying depth values depending on the method of sonde deployment at that station. For stations XHH4931 and XEF3551, a LAYER column value of 'B' indicates the sonde was deployed 0.3 meters above the bottom and a LAYER column value of 'S' indicates the sonde was deployed 1 meter below the surface. For station XFG4618, a LAYER column value of 'S' indicates the sonde was deployed 1 meter below the surface.

In the 2014 sonde data, there are numerous instances of turbidity measurements with negative values. The turbidity probe accuracy is plus or minus 5 NTU. In cases where turbidity probe post-deployment calibration values were within acceptable limits, negative values greater than or equal to -5.0 NTU are reported.

During 2014, it was not always possible, for logistical reasons, to replace sondes at all sites every two weeks, or every month for station XEF3551 (Gooses – Bottom) and station MZC0016 (Williston Lake Pier).

The sonde at station XHH3851 was not exchanged on 19-May-2014 and 3-Sep-2014.

The sonde at station XKH0375 was not exchanged on 24-April-2014, 21-May-2014, 30-Jun-2014, 11-Aug-2014, and 18-Sep-2014.

The sonde at station XDN6921 was not exchanged on 1-May-2014.

The sonde at station XFG2810 was not exchanged on 5-May-2014, 9-Jul-2014, and 23-Sep-2014.

The sonde at station XFG6431 was not exchanged on 10-April-2014, 5-May-2014, 9-Jul-2014, and 23-Sep-2014.

The sonde at station XEB5404 was not exchanged on 15-Apr-2014, 22-May-2014, 15-Jul-2014, 26-Aug-2014, 23-Sep-2014, and 15-Oct-2014.

The sonde at station WXT0013 was not exchanged on 4-Jan-2014 and 21-Aug-2014.

The sonde at station PXT0455 was not exchanged on 4-Jan-2014, 12-Jun-2014, 21-Aug-2014, and 6-Nov-2014.

The sonde at station XIF4935 was not exchanged on 6-May-2014.

The sonde at station XEA3687 was not exchanged on 15-Apr-2014, 22-May-2014, 15-Jul-2014, 26-Aug-2014, 23-Sep-2014, and 15-Oct-2014.

The sonde at station MTI0015 was not exchanged on 21-Aug-2014.

The sonde at station POK0187 was not exchanged on 7-May-2014.

The sonde at station XBF7904 was not exchanged on 6-May-2014, 2-Jun-2014, 10-Jul-2014, 13-Aug-2014, 25-Sep-2014, and 15-Oct-2014.

The sonde at station POK0009 was not exchanged on 7-May-2014.

The sonde at station POK0316 was not exchanged on 7-May-2014.

The sonde at station LMN0028 was not exchanged on 21-Oct-2014.

The sonde at station XHF0460 was not exchanged on 16-April-2014, 23-Jun-2014, 31-Jul-2014, 19-Aug-2014, and 8-Sep-2014.

The sonde at station XKH2949 was not exchanged on 24-April-2014, 21-May-2014, 30-Jun-2014, 11-Aug-2014, and 17-Sep-2014.

The sondes at station XHH4931 (surface and bottom) were not exchanged on 19-May-2014 and 3-Sep-2014.

The sonde at station XEF3551 (surface) was not exchanged on 31-Jan-2014, 20-Mar-2014, 18-Jun-2014, 29-Jul-2014, 2-Sep-2014, and 16-Oct-2014.

The sonde at station XEF3551 (bottom) was not exchanged on 17-Feb-2014, 14-Jun-2014, and 22-Sep-2014.

An aerator may have been intermittently deployed in 2014 near station XEA3687. Records for exact dates of deployment were not kept.

Data from station XFG6431 suggests that the sonde was moved twice by unauthorized personnel between 8-Jul-2014 and 14-Jul-2014.

Completeness_Report:

2014 Data from thirty-two continuous monitoring stations are available on-line.

The 2014 Continuous Monitoring project dataset includes twelve months of sonde records from the continuous monitoring stations: WXT0013 (Iron Pot Landing), PXT0455 (Jug Bay), XHH3851 (Sycamore Point), XIE4742 (Masonville Cove Pier) and XEF3551 (Gooses – Surface and Bottom).

Sonde data were collected for eleven months at station: XFG6431 (Harris Creek Upstream).

Sonde data were collected for ten months at stations: XFG4618 (Harris Creek Profiler – Surface) and XFG2810 (Harris Creek Downstream).

Nine month deployments occurred at stations: MTI0015 (Mataponi), XJG7035 (Otter Point Creek), and XDM4486 (Bishopville Prong).

Deployments at stations: XDN6921 (Grey's Creek), XHH4931 (Possum Point - Bottom and Surface), NPC0012 (Newport Creek), XBM8828 (Public Landing), XJI2396 (Budd's Landing), XEA3687 (Mattawoman), XEB5404 (Indian Head), POK0187 (Pocomoke City), XEJ2464 (Sharptown), POK0009 (Shelltown), POK0316 (Snow Hill), XBF7904 (St Georges Creek), XCI9167 (Tyaskin), XDJ8905 (Vienna), XIF4935 (Lynch Point), XIF7918 (Riverside), XKH2949 (Havre de Grace), and XKH0375 (Susquehanna Flats) lasted eight months.

Sondes were deployed seven months at station: XHF0460 (Sandy Point - South Beach).

Sonde data were collected for five months at station: LMN0028 (Little Monie Creek).

Sondes were deployed four months at station: MZC0016 (Williston Lake Pier).

In 2014, the full suite of nutrient samples were collected at stations: XHH3851 (Sycamore Point), XHH4931 (Possum Point - Surface), XEA3687 (Mattawoman), XEB5404 (Indian Head), XFG2810 (Harris Creek Downstream), and XFG6431 (Harris Creek Upstream). A subset of nutrients (Volatile Suspended Solids, Ammonium, Orthophosphate, Nitrite plus Nitrate, Total Dissolved Nitrogen, and Total Dissolved Phosphorus) were collected at stations: XJG7035 (Otter Point Creek), PXT0455 (Jug Bay), MTI0015 (Mataponi), WXT0013 (Iron Pot Landing), and LMN0028 (Little Monie Creek). Alkalinity was measured at stations: XFG2810 (Harris Creek Downstream), XFG6431 (Harris Creek Upstream), and XFG4618 (Harris Creek Profiler – Surface). Total Suspended Solids, chlorophyll, and pheophytin were collected at all stations.

The user may discover a few interruptions in sonde datasets. In most cases, these interruptions were related to short-term problems with sonde operation.

Station XFG2810 (Harris Creek Downstream) was removed from service between 14-Jan-2014 and 21-Apr-2014 due to concerns about ice and low temperatures. Station XFG2810 was also removed from service 16-Dec-2014 due to concerns about ice and low temperatures.

Station XFG6431 (Harris Creek Upstream) was removed from service between 14-Jan-2014 and 27-Mar-2014 due to concerns about ice and low temperatures. Station XFG6431 was also removed from service 16-Dec-2014 due to concerns about ice and low temperatures.

Station XHH4931 (Possum Point - Bottom and Surface) was not deployed until 3-Apr-2014 due to concerns about ice and low temperatures. Station XHH4931 was also removed from service 10-Nov-2014 due to concerns about ice and low temperatures.

Station XJG7035 (Otter Point Creek) was not deployed until 9-Apr-2014 due to concerns about ice and low temperature. Station XJG7035 was also removed from service 2-Dec-2014 due to concerns about ice and low temperatures.

Station MTI0015 (Mataponi) was not deployed until 2-Apr-2014 due to concerns about ice and low temperature. Station MTI0015 was also removed from service 18-Dec-2014 due to concerns about ice and low temperatures.

Station MZC0016 (Williston Lake Pier) was not deployed until 17-Jul-2014 and was removed from service on 14-Oct-2014.

Station LMN0028 (Little Monie) was not deployed until 16-Jul-2014 due to pier damage.

Station XFG4618 (Harris Creek Profiler – Surface) was removed from service 16-Dec-2014 due to concerns about ice and low temperatures.

There were gaps in the sonde data for a few stations for the following reasons.

Station XEJ2464 (Sharptown) is missing data from 6-May-2014 to 21-May-2014 and from 12-Aug-2014 to 27-Aug-2014 due to sonde setup errors.

Station XFG6431 (Harris Creek Upstream) is missing data from 18-Oct-2014 to 30-Oct-2014 due to equipment malfunction.

Station XIE4742 (Masonville Cove Pier) is missing data from 27-Mar-2014 to 9-Apr-2014, 28-May-2014 to 3-Jun-2014, and 12-Jun-2014 to 19-Jun-2014 due to sonde failures.

Station MTI0015 (Mataponi) is missing data from 26-Jun-2014 to 10-Jul-2014 and 16-Dec-2014 to 18-Dec-2014 due to sonde power failures.

Station XEF3551 (Gooses - Bottom) is missing data from 9-Jul-2014 to 21-Jul-2014, 17-Nov-2014 to 1-Dec-2014, and 19-Dec-2014 to 31-Dec-2014 due to equipment removed from service for repair.

Station XEJ2464 (Sharptown) is missing data from 28-May-2014 to 2-Jun-2014 and 15-Jul-2014 to 16-Jul-2014 due to sonde power failures.

Station XJI2396 (Budd's Landing) is missing data from 20-Jul-2014 to 31-Jul-2014 due to equipment malfunction.

Station XDJ8905 (Vienna) is missing data from 10-Aug-2014 to 12-Aug-2014 due to a sonde power failure.

Station XKH2949 (Havre de Grace) is missing data from 10-Aug-2014 to 21-Aug-2014 due to equipment malfunction.

Station XIF7918 (Riverside) is missing data from 27-Aug-2014 to 11-Sep-2014 due to equipment malfunction.

Station XDJ8905 (Vienna) is missing data from 9-Sep-2014 to 10-Sep-2014 due to equipment malfunction.

Station XKH0375 (Susquehanna Flats) is missing data from 7-Nov-2014 to 13-Nov-2014 due to equipment malfunction.

Station XJG7035 (Otter Point Creek) is missing data from 18-Nov-2014 to 2-Dec-2014 due to equipment malfunction.

Station XEF3551 (Gooses - Bottom) is missing data from 2-Apr-2014 to 28-Apr-2014 and 7-May-2014 to 14-May-2014 due to equipment malfunctions.

Station WXT0013 (Iron Pot Landing) is missing data from 15-Feb-2014 to 26-Feb-2014 and 2-May-2014 to 14-May-2014 due to sonde power failures.

Station MTI0015 (Mataponi) is missing data from 1-May-2014 to 14-May-2014 due to a sonde setup error.

Station NPC0012 (Newport Creek) is missing data from 8-Jul-2014 to 22-Jul-2014 and 18-Aug-2014 to 20-Aug-2014 due to equipment malfunctions.

Station POK0009 (Shelltown) is missing data from 2-Jun-2014 to 5-Jun-2014 due to a power failure.

Station XHF0460 (Sandy Point - South Beach) is missing data from 4-May-2014 to 12-May-2014 due to a power failure.

On a few occasions, due to extreme low tide conditions, sondes were not submerged. These data are not included in the published dataset.

All other missing sonde attribute values were removed because the data were determined to be unreliable during the quality control process.

Lineage:

Process_Step:

Process_Description:

SONDE CALIBRATION and POST-CALIBRATION

The Yellow Springs Instrument (YSI) 6600 V2 and EXO2 data sondes were maintained and calibrated before and after each deployment in accordance with YSI recommendations. [<http://www.ysi.com/support.php>]

FIELD MEASUREMENTS AND SAMPLING

SONDES:

The continuous monitoring sensors at the sites recorded seven water quality parameters every 15 minutes, except at stations XEF3551 and XFG4618. The surface and bottom monitors at station XEF3551 and the surface monitor at station XFG4618 sampled parameters at 60-minute intervals for the entire deployments. Data were uploaded to DNR's web site [<http://www.eyesonthebay.net>] shortly after retrieval.

At all sites the seven water quality parameters measured continuously were: water temperature, specific conductance (used to derive salinity values), dissolved oxygen, oxygen percent saturation, turbidity (NTU), fluorescence (used to estimate chlorophyll a) and pH. Sondes deployed at fixed depths also measured water depth.

Most monitoring stations were equipped with a YSI 6600 V2 sonde. One station (LMN0028) was equipped with a YSI EXO2 sonde. Both types of sonde logged data onto an internal memory, where it was stored until retrieval. Thirteen stations were equipped with cellular telemetry units, which allowed data to be transmitted hourly to a server computer at DNR. Sondes were deployed inside vertically-oriented four-inch diameter PVC pipes with several two-inch holes drilled along their length to allow for water exchange. Depending on location, sondes were either suspended from a float 1.0-meters below surface or fixed 0.3-meters or 0.5-meters above bottom resting on a stop bolt.

Sondes at station XIF4935 (Lynch Point) were deployed from a float at a depth of 1.0 meters below the surface between 9-Apr-2014 and 6-May-2014. Due to shallow water depths, sondes were deployed at a fixed depth of 0.3 meters above the bottom beginning 6-May-2014 and lasting until the station was removed for the year on 5-Nov-2014.

Sondes at the following stations were deployed at a fixed depth of 0.3 meters above the bottom: LMN0028 (Little Monie Creek), MTI0015 (Mataponi), NPC0012 (Newport Creek), PXT0455 (Jug Bay), WXT0013 (Iron Pot Landing), XBM8828 (Public Landing), XDM4486 (Bishopville Prong), XDN6921 (Grey's Creek), XEA3687 (Mattawoman), XEB5404 (Indian Head), XEF3551 (Gooses - Bottom), XHH4931 (Possum Point - Bottom), XJG7035 (Otter Point Creek), XKH0375 (Susquehanna Flats), XCI9167 (Tyaskin), XKH2949 (Havre de Grace), XFG2810 (Harris Creek Downstream), and XFG6431 (Harris Creek Upstream).

Sondes at station XBF7904 (St Georges Creek) were deployed at a fixed depth of 0.5 meters above the bottom.

All other sondes were deployed suspended from buoys at a depth of 1.0 meters below the surface.

Note that meters were deployed concurrently at two depths at stations: XEF3551, and XHH4931.

WATER QUALITY CALIBRATION SAMPLES:

Each time sondes were exchanged at each Continuous Monitoring station, "Grab" water quality samples were collected at 1.0 meter depth using a horizontal "Alpha" water sampler. At Station XFG4618, a second (bottom) grab sample was collected at 2.0m depth. Also, at station XEF3551, a second (bottom) grab sample was collected at 11.0m depth. At the time the water was collected, a Hydrolab sonde measurement was taken at 1.0 meter depth.

Numbered two-quart bottles were triple-rinsed and filled with water for "whole" and "filtered" nutrient and chlorophyll samples. (As noted previously, full suites of nutrient samples were not collected at all stations).

Nutrient, pigment and suspended-solid water samples were filtered on station or shortly thereafter. Sample waters and filters were placed on ice immediately after filtration.

Particulate samples included: Chlorophyll, Particulate Carbon, Particulate Nitrogen, Particulate Phosphorus (PP), Particulate Inorganic Phosphorous (PIP), Total Suspended Solids (TSS) and Volatile Suspended Solids (VSS).

Filtrate collected from TSS/VSS or PP/PIP filtrations was used for dissolved nutrient samples. Total Dissolved Nitrogen and Total Dissolved Phosphorus, Nitrate, Nitrite, Ammonium, Orthophosphate, and Dissolved Organic Carbon samples were collected.

HYDROLAB PROFILE:

The first reading of the Hydrolab water-column profile at each station was recorded at the same time the water quality "grab" sample was collected. After the 1.0-meter depth record was logged, the sonde was lowered to the bottom. A reading was taken at 0.3-meters above the bottom. The sonde was raised and measurements were recorded at 0.5-meter or 1.0-meter increments until it reached the surface. (In cases where station depth was greater than 3-meters, the sonde was raised in 1-meter increments).

SECCHI DEPTH:

Secchi Disk Depth was measured each time sondes were exchanged. Readings with the Secchi disk were made in-situ without the aid of sunglasses. The Secchi disk was lowered into the water, on the shady side of the boat or pier. The depth at which the disk was no longer visible was recorded. The time at which the reading was taken was noted. This facilitated later matching of Secchi depth readings with transmissometer and turbidity data.

PAR MEASUREMENT:

Underwater Photosynthetically Active Radiation (PAR, 400-700nm)

When meters were exchanged at a site, down-welling light penetrating the water column (PAR) was measured underwater at several depths to calculate the light attenuation coefficient,

Kd. Simultaneous surface and submersed PAR intensity measurements were taken to account for variability in incident surface irradiance due to changes in cloud cover. Data collected from this procedure were used to estimate the depth of the photic zone.

The equipment used was manufactured by LI-COR, Inc. and consisted of a LI-192SA, flat cosine Underwater Quantum Sensor, a LI-190SA air (deck) reference sensor and a Data Logger (LI-1000 or LI-1400).

Surface and underwater readings were recorded simultaneously. Readings were allowed to stabilize before being recorded. If the station depth was less than 3 meters, readings were taken at 0.1 meter and at 0.25-meter intervals until 10% for the 0.1-meter reading was reached. If the station depth was greater than 3 meters, a reading was taken at 0.1-meter and at 0.5-meter intervals until 10% of the 0.1-meter reading was reached.

PAR readings had also been collected at 15-minute intervals during deployment dates at station XBM8828 (Public Landing) between 2005 and 2012. All 2013 readings were considered invalid, however, due to equipment failure and the PAR sensor was not deployed in 2014.

SONDE DATA CHECKS

At most stations, the continuous monitoring sondes were retrieved, calibrated and replaced bi-weekly during deployment. Data Loggers deployed from November to March were exchanged monthly because less biofouling, which may compromise data integrity, occurs during cold weather months. Data loggers deployed greater than 10m below surface at station XEF3551 were exchanged monthly. Data loggers deployed in a contained lake at station MZC0016 were exchanged monthly. At each deployment, sondes were replaced with clean, recalibrated units and data from the data loggers were downloaded to a computer.

In the field, before an instrument was replaced, field staff allowed both the new (freshly calibrated) sonde and the old (deployed) sonde to log two readings (fifteen minutes apart at most stations) side by side at the same depth. For the surface and bottom sondes at station XEF3551 and the surface monitor at station XFG4618, only one simultaneous reading was taken using the new and old sondes. In addition at all of the stations, for one of the simultaneous readings, data were recorded from a discrete instrument -usually a Hydrolab sonde. This three-way comparison assured that the "new" and "old" sondes were both reading each parameter within a certain tolerance. The Hydrolab reading was used as a "double-check," and since it was a discrete reading, it allowed staff to watch the display and note whether the parameters were fluctuating or stable.

EcoWatch(tm) software (a YSI product) was used to calibrate the YSI 6600 V2 instruments, as well as to upload and view data collected. KOR(tm) software (a YSI product) was used to calibrate the EXO2 instruments, as well as to upload and view data collected. Data downloaded from the sonde were subjected to quality assurance/quality control checks to ensure that values outside the range of possibility were not displayed on the DNR web site.

Data were evaluated using both three-way in-situ comparison results and data from sonde calibrations. The comparison tolerances were as follows - for both pre- and post-calibration and in-situ comparisons: Temperature (deg C) +- 0.2; Specific Conductance (uM/cm) +- 5%; Dissolved Oxygen (mg/l) +- 0.5 mg/l; pH +- 0.2; Turbidity (NTU) +- 5% or 5.0 NTU (whichever is greater); Chlorophyll (ug/l) +- 5% or 5.0 ug/l (whichever is greater).

Excessive drift between pre- and post- calibration values of sonde probes, variance from in-situ measurements or probe failures caused data to be flagged. When post-calibration drift exceeded the limits stated above in both the post-calibration and the in-situ comparables, the "bad data" were masked within the data set with an error code (see QAPP for list of error codes).

SONDE FILE POST-PROCESSING:

Each "raw" .csv file of sonde data was post-processed using an Excel(tm) Macro. The file was opened and renamed. Rows of data acquired before and after deployment were deleted. Records (if any) were also deleted if instrument error codes indicated "garbage" data. The macro rearranged columns and inserted error-tracking columns and headings. Macro statements flagged negative values, missing values and highlighted values outside each parameter's normal range. The macro also returned a report summarizing range exceedances. Event and instrument information was appended to each record.

Flagged values were evaluated. Common anomalies included spikes in fluorescence and turbidity, dips in specific conductance, and extremely high dissolved oxygen readings. Instrument post-calibration results, in-situ comparisons with Hydrolab, LI-COR readings, historical data from nearby locations, and survey crew remarks were used to determine whether sensor values were acceptable.

In cases where data were determined to be unreliable, the reason(s) were documented with error codes and comments. Unreliable data were masked. No data were discarded. Only data considered reliable were published in reports.

Field staff and Tawes Office staff reviewed continuous monitoring data weekly. If a problem was identified, a field team member was dispatched to replace the instrument as soon as possible.

VERIFICATION AND DATA MANAGEMENT

At the end of the monitoring season, DNR Tawes Office and Field Office personnel conducted additional data QA/QC procedures. All of the data were plotted and outliers and anomalous values were thoroughly researched. Staff compared unusual values to historic values from the site and values from nearby sites in the Bay. Weather events were considered, event logs were reviewed, and field staff members were consulted regarding possible legitimate causes for the values. In cases where values were not considered legitimate, error codes were assigned. All data were retained in the archive data set. After field staff and the Quality Assurance Officer reviewed error flags, the values were masked within the published dataset.

Process_Date: Unknown

Process_Contact:

Contact_Information:

Contact_Person_Primary:

Contact_Person: Sally Bowen

Contact_Position: Project Chief, Monitoring Field Office, DNR

Contact_Address:

Address_Type: mailing and physical

Address: 1919 Lincoln Drive

City: Annapolis

State_or_Province: Maryland

Postal_Code: 21401

Country: USA

Contact_Voice_Telephone: 410 263-3369

Contact_Electronic_Mail_Address: Sally.Bowen_nospam_@maryland.gov[Remove_nospam_ for valid email address]

Process_Step:

Process_Description:

Laboratory analysis - CBL

University of Maryland's Chesapeake Biological Laboratory (CBL), Nutrient Analytical Services Laboratory analyzed total dissolved nitrogen, particulate nitrogen, nitrite, nitrite + nitrate, ammonium, total dissolved phosphorus, particulate phosphorus, particulate inorganic phosphorus, orthophosphate, dissolved organic carbon, particulate carbon, total suspended solids, volatile suspended solids, and alkalinity.

Note that in 2014, the full suite of nutrients were only collected at stations: XHH3851 (Sycamore Point), XHH4931 (Possum Point - Surface), XFG2810 (Harris Creek Downstream), XFG6431 (Harris Creek Upstream), XEA3687 (Mattawoman), and XEB5404 (Indian Head). A sub-set of nutrients (Volatile Suspended Solids, Ammonium, Orthophosphate, Nitrite plus Nitrate, Total Dissolved Nitrogen, and Total Dissolved Phosphorus) were collected at stations XJG7035 (Otter Point Creek), PXT0455 (Jug Bay), MTI0015 (Mataponi), WXT0013 (Iron Pot Landing), and LMN0028 (Little Monie Creek). Alkalinity was collected at stations: XFG2810 (Harris Creek Downstream), XFG6431 (Harris Creek Upstream), and XFG4618 (Harris Creek Profiler – Surface). Total Suspended Solids, chlorophyll, and pheophytin were collected at all stations.

Note that beginning in 2008, Shallow Water Monitoring silicate samples were only collected and analyzed for four Maryland Coastal Bays stations: XDM4486 (Bishopville Prong), XDN6921 (Grey's Creek), NPC0012 (Newport Creek) and XBM8828 (Public Landing). Beginning in 2012, silicate samples were no longer collected at these four Coastal Bays stations.

Further information about laboratory analytical procedures may be obtained from the "Process_Contact".

Process_Date: Unknown

Process_Contact:

Contact_Information:

Contact_Person_Primary:

Contact_Person: Jerry Frank

Contact_Position: Director of Analytical Services/Quality Assurance Officer

Contact_Address:

Address_Type: mailing and physical

Address: Chesapeake Biological Laboratory, 146 Williams St; P.O. Box 38

City: Solomons

State_or_Province: Maryland

Postal_Code: 20688

Country: USA

Contact_Voice_Telephone: 410 326-7252

Contact_Electronic_Mail_Address: frank_nospam_@cbl.umces.edu[Remove _nospam_ for valid email address]

Spatial_Data_Organization_Information:

Indirect_Spatial_Reference: Assawoman Bay, Back River, Bush River, Chesapeake Bay, Chincoteague Bay, Maryland Coastal Bays, Choptank River, Corsica River, Harris Creek, Mattawoman Creek, Nanticoke River, Patapsco River, Patuxent River, Pocomoke River, Potomac River, Sassafras River, Susquehanna River, Susquehanna Flats, Wicomico River, Williston Lake, Maryland, USA

Direct_Spatial_Reference_Method: Point

Spatial_Reference_Information:

Horizontal_Coordinate_System_Definition:

Geographic:

Latitude_Resolution: 0.0001

Longitude_Resolution: 0.0001

Geographic_Coordinate_Units: Decimal degrees

Geodetic_Model:

Horizontal_Datum_Name: North American Datum of 1983

Ellipsoid_Name: Geodetic Reference System 80

Semi-major_Axis: 6378137

Denominator_of_Flattening_Ratio: 298.257

Entity_and_Attribute_Information:

Overview_Description:

Entity_and_Attribute_Overview:

This metadata record is a description of a continuous monitoring project. Project data are an aggregation of data collected at thirty-two Maryland stations during 2014.

The data are contained in six related entities (tables): Station_Information, Monitoring_Event_Data, Water_Quality_Data, Light_Attenuation_Data, Optical_Density_Data, and CMON_DATA. Each table contains attributes (fields).

The entity Station_Information is comprised of the attributes: Station, Station_Description, USGS_Gage, CBSEG_2003, CBSEG_2003_Description, CB_Segment_Shed_2009, CB_Segment_Shed_2009_Description, HUC12, FIPS, State, County_City, FallLine, Latitude, Longitude, UTMX, UTM Y, and LL_Datum.

The entity Monitoring_Event_Data is comprised of the attributes: Event_Id, Source, Agency, Program, Project, Station, Event_Start_Date, Event_Start_Time, Cruise, Total_Depth, Upper_Pycnocline, Lower_Pycnocline, Wind_Speed, Wind_Direction, Precip_Type, Tide_Stage, Cloud_Cover, Gauge_Height, Pressure, Flow_Stage, and Details.

The entity Water_Quality_Data is comprised of the attributes: EventId, Source, Project, Station, SampleDate, SampleTime, Total_Depth, Layer, SampleType, SampleReplicateType, Parameter, Qualifier, MeasureValue, Unit, Method, Lab, Problem, Details, Depth, UpperPycnocline, LowerPycnocline, Lat, and Long.

The entity Light_Attenuation_Data is comprised of the attributes: Event_Id, Source, Station, Station_Description, Program, Project, Sample_Date, Sample_Time, Sample_Replicate_Type, SubstanceIdentificationName, Depth, Unit, Method, Details, Upper_Pycnocline, and Lower_Pycnocline.

The entity Optical_Density_Data is comprised of the attributes: Event_Id, Source, Station, Station_Description, Program, Project, Sample_Date, Sample_Time, Sample_Replicate_Type, SubstanceIdentificationName, Depth, Unit, Method, Details, Upper_Pycnocline, and Lower_Pycnocline.

The entity CMON_DATA is comprised of the attributes: Station, Date, Time (EST), Date+Time, DO (conc), DO (percent), Salinity (ppt), Temp (deg C), Temp (deg F), pH, Turbidity (NTU), and Chlorophyll a (ug/l).

Entity_and_Attribute_Detail_Citation:

Water Quality Database - Database Design and Data Dictionary Prepared For: U.S. Environmental Protection Agency, Region III, Chesapeake Bay Program Office, January 2004. [http://www.chesapeakebay.net/documents/3676/cbwqdb2004_rb.pdf]

The most current version of the Water Quality Data Dictionary - Online may be found at: [http://archive.chesapeakebay.net/data/data_dict.cfm?DB_CODE=CBP_WQDB]

Guide to Using Chesapeake Bay Program Water Quality Monitoring Data, EPA 903-R-12-001, February 2012, CBP/TRS 304-12 [http://www.chesapeakebay.net/documents/3676/wq_data_userguide_10feb12_mod.pdf]

Quality Assurance Project Plan for the Maryland Department of Natural Resources, Chesapeake Bay Shallow Water Quality Monitoring Program, for the period July 1, 2014 - June 30, 2015.

[http://mddnr.chesapeakebay.net/eyesonthebay/documents/SWM_QAPP_2014_2015_Draft_v3.pdf]

Distribution_Information:

Distributor:

Contact_Information:

Contact_Person_Primary:

Contact_Person: Michael Mallonee

Contact_Position: Water Quality Database Manager

Contact_Address:

Address_Type: mailing

Address: 410 Severn Avenue, Suite 109

City: Annapolis

State_or_Province: Maryland

Postal_Code: 71403

Contact_Voice_Telephone: 800 968-5785

Contact_Electronic_Mail_Address: mmallone@_no_spam_chesapeakebay.net[Remove _nosspam_ for valid email address]

Resource_Description: Downloadable data

Distribution_Liability: None of the Chesapeake Bay Program partners or any of their employees, contractors, or subcontractors makes any warranty, expressed or implied, nor assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information or data contained within the web site. Reference to any specific commercial products, processes, or services or the use of any trade, firm, or corporation name is for the information and convenience of the public and does not constitute endorsement, recommendation or favoring by the Chesapeake Bay Program partners.

Standard_Order_Process:

Digital_Form:

Digital_Transfer_Information:

Format_Name: ASCII file, formatted for text attributes, declared format

Format_Information_Content: Station Information data, Monitoring Event data, Light Attenuation data and Water Quality data

File-Decompression_Technique: No compression applied

Transfer_Size: 2.2

Digital_Transfer_Option:

Online_Option:

Computer_Contact_Information:

Network_Address:

Network_Resource_Name:

[http://www.chesapeakebay.net/data/index.cfm?subjectarea=WATER_QUALITY]

Access_Instructions: Station Information, Monitoring Event, Light Attenuation and Water Quality data are available through the Chesapeake Bay Programs CIMS data hub. Select Water Quality Database (1984-Present). Access the data by following web site (see network resource name) instructions.

Digital_Form:

Digital_Transfer_Information:

Format_Name: ASCII file, formatted for text attributes, declared format

Format_Information_Content: Continuous monitoring sonde data

File-Decompression_Technique: No compression applied

Transfer_Size: 100

Digital_Transfer_Option:

Online_Option:

Computer_Contact_Information:

Network_Address:

Network_Resource_Name:

[http://mddnr.chesapeakebay.net/newmontech/contmon/archived_results2.cfm?year=2014]

Access_Instructions: CMON data (sonde data) for 2014 are available through the Continuous Monitoring - Archived Results page of Eyes on the Bay website. Access sonde data by following web site (see network resource name) instructions. Select station and specify dates. Station record set counts range from 6,334 to 35,040. Depending on connection speed, downloads may take a considerable amount of time. Downloading partial record sets will proceed more quickly.

Fees: None

Metadata_Reference_Information:

Metadata_Date: 20150424

Metadata_Contact:

Contact_Information:

Contact_Person_Primary:

Contact_Person: Brian Smith

Contact_Address:

Address_Type: Mailing and physical address

Address: MDDNR, 580 Taylor Ave, D-2

City: Annapolis

State_or_Province: MD

Postal_Code: 21401

Contact_Voice_Telephone: (410) 260-8630

Contact_Electronic_Mail_Address: brianr.smith_nospam_@maryland.gov[Remove_nospam_ for valid email address]

Metadata_Standard_Name: Content Standards for Digital Geospatial Metadata

Metadata_Standard_Version: FGDC-STD-001-1998