

UNCLASSIFIED

UNCLASSIFIED



Background

Objectives of the effort Team and Partnerships

Modeling approach

Hydrodynamics

Nutrient water quality

Sediment transport

Model applications

Dredging scenarios

Extreme event scenarios

Project and reporting schedule

Questions







SITE OVERVIEW

Conowingo Reservoir:

Lowest impoundment on the Susquehanna 94' tall dam (owned by Constellation Corp.) 9,000 acre impoundment

Concern:

Increased risk of intense summer and winter season storms leading to increased risk of sediment and nutrient releases to Chesapeake Bay

Previous Models:

- -proprietary
- -lack of spatial sediment capability
- -not integratable (as is) to CBP models










- 1. Develop a non-proprietary, 3D water quality modeling system of Conowingo Reservoir for the purpose stated above. The modeling system should be capable of simulating hydrodynamics, biogeochemical, and sediment transport processes within CR. Modeling package output will be consistent with requirements of the CBP modeling suite.
- Application of the modeling system to current and future dredging scenarios, specifically the
 evaluation of sediment and associated nutrient reductions from different dredging scenarios.
 It must leverage the additional CR sediment characterization work done and lessons learned
 through Maryland's innovative and beneficial reuse pilot.
- 3. Application of the modeling system to future hydrologic-climate scenarios. This information will help various Chesapeake Bay partnerships better understand and institutionalize the resiliency and response of CR to extreme weather events, flows, future climate change hydrology, and determine CR scour and sediment resuspension and associated nutrient/contaminant increases within the reservoir and transport downstream.



TEAM AND PARTNERSHIPS








MODEL REQUIREMENTS



- Continuous simulation of the reservoir pool including selected hydrometeorological events; (1991-2000)
- Change in hydrodynamics from reservoir infill of sediments from the CR watershed, and removal of material through dredging
- Biogeochemistry in the reservoir pool, responding to the amount and speciation of nitrogen, phosphorus, and sediment inputs from upstream and bottom sediment
- Biogeochemical changes in sediments, including burial, species changes, and water column exchanges
- Physical changes in sediment characteristics due to erosion, bed armoring, and deposition of sediment and the resulting morphological changes in the reservoir
- Dredging of the reservoir.





MODELING APPROACH – DATA ACQUISITION



- Bathymetry in the model domain, i.e., the CR.
- Meteorological data time series wind speed and direction atmospheric pressure incident solar radiation air temperature (both wet and dry bulb) precipitation
- Hydrologic data time series for watershed CBP will provide Phase 6 → Phase 7 Constellation Energy for dam operations (Muddy Run)
- Water quality in-situ water temperature, DO, SOD, nitrogen, phosphorus, and other
- Sediment characteristics grain size distributions (including percentage of organic matter) historical cores and new collection for erodibility

| Description | | FY | 25 | |
|-------------------|----|----|----|----|
| • | Q1 | Q2 | Q3 | Q4 |
| DATA ACQUISISTION | X | | | |



MODELING APPROACH



Modeling approach

Hydrodynamics Nutrient water quality Sediment transport Baseline calibration

Model Selection

Environmental Fluid Dynamics Code+ (EFDC+) Based on EFDC (originally developed by John Hamrick @ VIMS)

- Refined by DSI,LLC
- Open source
- 3D hydrodynamics that uses a curvilinear (structured) grid
- Fully coupled hydrodynamics, sediments, water quality

| Description | FY25 | | | | | | | | |
|------------------------|------|----|----|----|--|--|--|--|--|
| • | Q1 | Q2 | Q3 | Q4 | | | | | |
| DEVELOPMENT OF | | | | | | | | | |
| CRMS | | | | | | | | | |
| Hydrodynamics | Х | X | | | | | | | |
| Nutrient Water Quality | | Х | Х | Х | | | | | |
| Sediment Transport | | Х | Х | Х | | | | | |





MODELING APPROACH - HYDRODYNAMICS






Major Inflows

Holtwood Dam (Upstream) Muddy Run Power Reservoir Operational boundary Watershed Direct runoff Initiate with Phase 6 HSPF Upgrade to Phase 7



Major Outflows

Muddy Run Power Reservoir Conowingo Dam (Downstream) outlet grid constructed to mesh with CBP model








First Version of the model has:

- 49,051 horizontal grid cells
- 10 vertical sigma layers in each grid cell

Second version will have fewer horizontal grid cells.



UNCLASSIFIED





Time: 1991-01-01 00:00 L = 18980; I,J = 778, 82 X, Y (m): 399227.483, 4390455.539 dX, dY (m): 27.422, 24.147 Bot EL (m): 13.1839

Depth (m): 20.0961 Structure BC ID = Conowingo Dam

13









COARSE GRID







MODELING APPROACH – SEDIMENT TRANSPORT



- Model will represent the different bed layer sources as scour occurs during different limbs of the hydrograph
- Will simulate the different classes and composition of sediment as well what's eroded into the water column
- Use field observations to set up the sediment bed model vertical variation of the different components - with spatial variation in the vertical composition in different parts of the reservoir

Data development:

- Historical cores with chemical analysis
- Additional data collection for erosion rates with SEDFLUME Facilitated through MDE 30 sediment grabs 4x5 gal buckets

Model runtime:

1 week for EFDC+ Model emulation may be used for linkage to Bay model



SEDIMENT SAMPLING


Sampling supports 2 needs:


SEDFLUME

- Ponar grab samples for grain size distribution (green)
- 4x 5GAL Buckets for SEDFLUME (red)
- Push core/gravity core (red)

BOD → sediment carbon fractionation

Surficial Eckman dredge (red)







MODELING - NUTRIENT WATER QUALITY



Based in CE-QUAL-ICM kinetics

Unlimited algae and macrophyte groups mostly defined through half-saturation and uptake rates utilizes temperature effects on coefficients

Carbon treatment

DOC

Labile G1

Refractory G2+G3

Processes


reaeration

benthic mass fluxes\sediment diagenesis (DiToro kinetics) can be spatially varying

Boundaries

point sources wet/dry deposition

| ID | Description |
|----|---|
| 1 | Refractory Particulate Organic Carbon |
| 2 | Labile Particulate Organic Carbon |
| 3 | Dissolved Organic Carbon |
| 4 | Refractory Particulate Organic Phosphorus |
| 5 | Labile Particulate Organic Phosphorus |
| 6 | Dissolved Organic Phosphorus |
| 7 | Total Phosphate |
| 8 | Refractory Particulate Organic Nitrogen |
| 9 | Labile Particulate Organic Nitrogen |
| 10 | Dissolved Organic Nitrogen |
| 11 | Ammonia Nitrogen |
| 12 | Nitrate Nitrogen |
| 13 | Particulate Biogenic Silica |
| 14 | Dissolved Available Silica |
| 15 | Chemical Oxygen Demand |
| 16 | Dissolved Oxygen |
| 17 | Total Active Metal |
| 18 | Fecal Coliform |
| 19 | Carbon Dioxide |
| 20 | Cyanobacteria |
| 21 | Diatoms |
| 22 | Green Algae |
| 23 | Macrophytes |
| 24 | MesoZooplankton |





APPLICATIONS – DREDGING SCENARIOS



Continuous simulation period (of 1991-2000)

Dredging 1 & 2: Different dredging scenarios in different locations in the CR to determine associated nutrients reduction within the CR and transported to Chesapeake Bay

Infill 1& 2: Different infill scenarios based on availably of bathymetry (e.g., 1995 and 2010 conditions or other years depending on data availability).

Reduced loading: A scenario that simulates watershed BMPs and in-reservoir dredging to reduce sediment loading from CR to Chesapeake Bay.

| Description | | FY | ′ 25 | | FY26 | | | | | |
|------------------------------------|--|----|-------------|----|------|----|----|----|--|--|
| • | | Q2 | Q3 | Q4 | Q1 | Q2 | Q3 | Q4 | | |
| DEVELOPMENT AND | | | | | | | | | | |
| SIMULATION OF | | | | | | | | | | |
| DREDGING SCENARIOS | | | | | | | | | | |
| dredging 1 | | | | Х | Х | Х | Х | | | |
| dredging 2 | | | | Χ | Х | Х | Х | | | |
| Infill 1 | | | | Х | Х | Х | Х | | | |
| Infill 2 | | | | Х | Х | Х | Х | | | |
| Reduce sediment loading to ChesBay | | | | Х | X | Х | Х | | | |



APPLICATIONS – EXTREME EVENT SCENARIOS



Scenario selection Q1 FY25

Initial loads:

Based on 1991-2000 hindcast

Critical period:

1993-1995

Scenario characteristics:

Two back-to-back extreme storms (probably in excess of 400,000 cfs) during the warm season (April-September) in close succession

| Description | | FY | ′ 25 | | FY26 | | | | |
|-----------------|----|----|-------------|----|------|----|----|----|--|
| | Q1 | Q2 | Q3 | Q4 | Q1 | Q2 | Q3 | Q4 | |
| DEVELOPMENT AND | | | | | | | | | |
| SIMULATION OF | | | | X | | X | | | |
| EXTREME EVENT | | | | ^ | ^ | ^ | ^ | | |
| SCENARIOS | | | | | | | | | |





PROJECT AND REPORTING SCHEDULE



| Description | FY25 | | | | | FY | '26 | | FY27 | | | | |
|-------------------------|------|----|----|----|----|----|------------|----|------|----|----|----|--|
| • | Q1 | Q2 | Q3 | Q4 | Q1 | Q2 | Q3 | Q4 | Q1 | Q2 | Q3 | Q4 | |
| DATA ACQUISISTION | Χ | | | | | | | | | | | | |
| DEVELOPMENT OF | | | | | | | | | | | | | |
| CRMS | | | | | | | | | | | | | |
| Hydrodynamics | Х | X | | | | | | | | | | | |
| Nutrient Water Quality | | Χ | X | X | | | | | | | | | |
| Sediment Transport | | Х | Х | X | | | | | | | | | |
| DEVELOPMENT AND | | | | | | | | | | | | | |
| SIMULATION OF | | | | | | | | | | | | | |
| DREDGING SCENARIOS | | | | | | | | | | | | | |
| dredging 1 | | | | X | Χ | X | Х | | | | | | |
| dredging 2 | | | | X | Χ | X | Х | | | | | | |
| Infill 1 | | | | X | Χ | X | X | | | | | | |
| Infill 2 | | | | Х | Χ | Х | Х | | | | | | |
| Reduce sediment loading | | | | X | Х | Х | X | | | | | | |
| to ChesBay | | | | ^ | ^ | ^ | ^ | | | | | | |
| DEVELOPMENT AND | | | | | | | | | | | | | |
| SIMULATION OF | | | | X | Х | Х | X | | | | | | |
| EXTREME EVENT | | | | | ^ | | ^ | | | | | | |
| SCENARIOS | | | | | | | | | | | | | |

CBP phase 7



PROJECT AND REPORTING SCHEDULE



| FY25 | | | | FY26 | | | FY27 | | | | |
|------|----|-------|----------|-------------------------------|---|---|--|---|---|---|--|
| Q1 | Q2 | Q3 | Q4 | Q1 | Q2 | Q3 | Q4 | Q1 | Q2 | Q3 | Q4 |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | Х | | | | | | | | |
| | | | | Χ | | | | | | | |
| | | | | Х | | | | | | | |
| | | | | | | | ~ | | | | |
| | | | | | | | ^ | | | | |
| | | | | | | | > | | | | |
| | | | | | | | ^ | | | | |
| | | | > | | | | \ | | | | |
| | | | ^ | | | | ^ | | | | |
| | | | | | | | | X | | | |
| | | | | | | Χ | Χ | Χ | Χ | | |
| | Q1 | Q1 Q2 | Q1 Q2 Q3 | Q1 Q2 Q3 Q4 X X X X X X | Q1 Q2 Q3 Q4 Q1 <td>Q1 Q2 Q3 Q4 Q1 Q2 <td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 </td><td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 </td><td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 Q1 <</td><td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 Q1 Q2 </td><td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 Q1 Q2 Q3 A</td></td> | Q1 Q2 Q3 Q4 Q1 Q2 <td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 </td> <td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 </td> <td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 Q1 <</td> <td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 Q1 Q2 </td> <td>Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 Q1 Q2 Q3 A</td> | Q1 Q2 Q3 Q4 Q1 Q2 Q3 | Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 | Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 Q1 < | Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 Q1 Q2 | Q1 Q2 Q3 Q4 Q1 Q2 Q3 Q4 Q1 Q2 Q3 A |

CBP phase 7

CONNECT WITH US

Jodi Ryder

Research Civil Engineer Environmental Laboratory

U.S. Army Engineer Research and Development Center
U.S. Army Corps of Engineers

Jodi.L.Ryder@usace.army.mil

601-631-1852





Scan this QR code with your phone for instant access





