Lower Susquehanna River Watershed Assessment

- The EPA Chesapeake Bay program and the Baltimore District USACE are working in parallel with a lot of cross-over.
- We have four categories of model runs:
 - Step 1 Remove Conowingo Reservoir from the system. This approach assumes instantaneous equilibrium between loads entering and leaving the reservoir.

Lower Susquehanna River Watershed Assessment


- Step 2 Add scour to WSM representation of Conowingo Reservoir. The scour is calibrated for two cases:
 - 0% N, 50% P, 100% TSS increase in annual loads
 - 0% N, 70% P, 250% TSS increase in annual loads
- Scour for January 1996 event derived from ADH simulation of Conowingo Reservoir (CFC's favorite). Three bathymetries:
 - Current (2011) bathymetry
 - After 1996 scour event

Lower Susquehanna River Watershed Assessment

- Reservoir-full conditions
- Step 3 Move the January 1996 storm event to alternate seasons of the year. Scour for one storm event from WSM with scour calibrated for 0% N, 50% P, 100% TSS increase in annual loads
- Each approach has its "pros and cons." The single event with scour based on ADH is the most realistic. Commonalities persist through all approaches. We'll have to reach a consensus on the ultimate effects.


Background


- ADH is the premier tool for computing sediment erosion, deposition, and transport in Conowingo Reservoir.
- The ADH application period, 2008 2011, contains two erosion events: Tropical Storm Lee and a small event in March 2011.
- We have three ADH runs based on alternate bathymetry:
 - Existing (2011) bathymetry,
 - Projected "Reservoir Full" bathymetry,
 - Bathymetry surveyed following 1996 scour event.
- ADH is not presently applied over our water quality simulation period, 1991 2000. We need a way to map computed erosion from 2011 to 1996.





The greatest flow during TS Lee occurs on Day 255, the second day on which flow exceeds the criteria for scour: 11,000 m³/s.

The greatest scour occurs on Day 254, the first day on which flow exceeds 11,000 m³/s. After that, the bed armors.












- •Solids loads for January 1996 are based on excess volume. Interpolate between two events calculated for 2011.
- •Nutrient and carbon loads based on bottom composition: 5% C, 0.3% N, 0.1%P.
- •Add the scour loads to the WSM loads. No other adjustment to the WSM loads.


TSS Scour from ADH





Cumulative Deposition















Model Results




- Let's concentrate on the TMDL (WIP) run.
- We'll look at time series at CB3.3C and at spatial plots in summer 1996 (first summer after storm).













Years













What's happening? Nutrients from the scour event deposit in bottom sediments and persist for years. Solids from scour event are inert after deposition.









Let's Switch Gears


- We have been examining the effect of an erosion event. What about the timing of the event?
- CBP has produced hydrodynamics and WSM runs that move the 1996 storm to different months.


Timing of Storm Event


- The following runs have been completed in addition to a run with scour from the January 1996 storm:
 - No winter storm
 - Storm moved to June
 - Storm moved to October
- These runs examine the effect of the entire event including runoff and scour!


Scour Computed by Two Models


Scour	TSS (tons)	N (tons)	P (tons)
Jan 1996, ADH	2,107,311	6,322	2,107
Jan 1996, HSPF	1,837,861	588	2,141






































Marginal Effect of January Storm










Marginal Effect of January Storm









Marginal Effect of January Storm







Step 1 - Basis for Scenarios

- Our first approach to examining the effect of Conowingo infill is to eliminate it from the WSM system.
- The system is full. No more settling.
- The WQM receives loads directly from the Susquehanna River plus local loads to the Conowingo Reservoir.





Difference plot showing effect of eliminating Conowingo.







Difference plot showing effect of eliminating Conowingo.






Difference plot showing effect of eliminating Conowingo.





Base TMDL simulation shown in red.




Step 1 Runs – Current Thoughts

- The continuous spillage is more harmful to water quality than a scour event. Excess loading occurs continuously, including the periods of critical water quality.
- The ADH runs suggest continuous spillage is not a good picture. ADH suggests deposition occurs even when the reservoir is "full."
- I can't completely dismiss these runs.


CBP Three-Step Program


- Step 2 Scour in Conowingo Reservoir
 - Try to match two reported outcomes.
 - 0% N, 50% P, 100% TSS increase in annual loads (Hirsch estimate of change from 1996 2001).
 - 0% N, 70% P, 250% TSS increase in annual loads (Hirsch citation of Langland and Hainly 1997 report).
 - Erosion implemented in Conowingo section of CBP Watershed Model.
 - Settling remains implemented between scour events.
 - Simulations for 2010 Progress Run (existing conditions) and TMDL (future conditions).



Difference plot showing effect of Step 2 scour events.


Difference plot showing effect of scour from a single storm.






Difference plot showing effect Step 2 scour events.


Difference plot showing effect of scour from a single storm.







Difference plot showing effect Step 2 scour events.

Difference plot showing effect of scour from a single storm.






Base TMDL simulation shown in red.




Step 2 Runs – Current Thoughts



- As expected, the effect of multiple scour events is worse than the effect of a single event.
- These are the least realistic of the runs we have conducted. The frequency and magnitude of scour events is unreasonable.

Step 2 Runs – Current Thoughts



- The HSPF model does not consider bed armoring or feedback between bathymetry changes and scour.
- We need to carefully examine and interpret forecasts that call for annual load increases of 50% P, 100% TSS or more.