Lower Susquehanna River Watershed Assessment

"Sediment Behind the Dams"

Parallel Studies

- Baltimore District USACE
 - 2008 2011 application period.
 - ADH hydrodynamic and sediment transport model for Conowingo Reservoir and Susquehanna Flats
 - HEC-RAS hydrodynamic and sediment transport model for Lakes Clarke and Aldred.
 - CBEMP for Chesapeake Bay.

Parallel Studies

Objectives

- Evaluate strategies that will maintain or decrease sediment and associated nutrient delivery to Chesapeake Bay.
- Prioritize strategies that will reduce the volume of sediment and associated nutrients available for transport during high-flow storm events.
- Determine the impacts of the loss of sediment and nutrient storage capacity behind Conowingo Dam to the Chesapeake Bay.

Parallel Studies

- USEPA Chesapeake Bay Program
 - 1991 2000 application period.
 - HSPF model for Conowingo Reservoir.
 - CBP Watershed Model for remainder of watershed.
 - CBEMP for Chesapeake Bay.
 - Objective
 - Assess impact of reservoir filling and scouring on Chesapeake Bay following implementation of TMDL's.

CBP Three-Step Program


- Step 1 Eliminate Conowingo Reservoir
 - The reservoir is full, residence time is short, settling is negligible.
 - Simulates a period with no erosion.
 - Simulations for 2010 Progress Run (existing conditions) and TMDL (future conditions).

CBP Three-Step Program

- Step 2 Scour in Conowingo Reservoir
 - Try to match two reported outcomes.
 - 0% N, 50% P, 100% TSS increase in annual loads (Hirsch estimate of change from 1996 2001).
 - 0% N, 70% P, 250% TSS increase in annual loads (Hirsch citation of Langland and Hainly 1997 report).
 - Erosion implemented in Conowingo section of CBP Watershed Model.
 - Settling remains implemented between scour events.
 - Simulations for 2010 Progress Run (existing conditions) and TMDL (future conditions).

CBP Three-Step Program

- Step 3 Evaluate Impact of Major Events
 - Move the January 1996 "Big Melt" to spring/summer.
 - Requires new CH3D hydrodynamic runs based on new storm periods.
 - 1996 without flood.
 - 1996 with flood in January.
 - 1996 with flood in June.
 - Six runs planned. TMDL loads with and without reservoir filled for the three hydrodynamic conditions.
 We need to review what we mean by "reservoir filled." 100% TSS increase or 250% TSS increase?




Step 1 - Basis for Scenarios


- No scouring occurs in the model. Limited scouring during the application period is expected in any event.
- The reservoir acts as a sink for solids (and nutrients in solid form).
- Our first approach to examining the effect of Conowingo infill is to eliminate it from the WSM system.
- The WQM receives loads directly from the Susquehanna River plus local loads to the Conowingo Reservoir.


Step 1 - Scenario Conditions

- Ten years hydrology, 1991 2000.
- Base conditions from the 2010 TMDL (land use, point sources, atmospheric loads etc.).
- Phase 5.3.2 Watershed Model.
- The same phase of the WSM and same calibration status of the WQM as used for TMDL determination.
- Scenario conditions eliminate Conowingo Reservoir.





A large fraction of the nitrogen loads is as nitrate and is unaffected by settling or scour.







The majority of the phosphorus load is in particulate form. In our model, PIP is considered to be inert.






Volatile solids are largely formed by primary production in the reservoir. When we take out the reservoir, we eliminate primary production. Volatile solids are a negligible portion of the total solids, in any event.





Examine key water quality constituents at four mainstem stations.


Focus on differences: Scenario – Base.





5 Years


3


5 Years


























Examine summer-average (June – August) concentrations of key water quality constituents along the mainstem axis.


Focus on differences: Scenario – Base.


1996 is "wet" hydrology, 1999 is "dry" hydrology.

















Examine equilibrium SAV area in CB1TF and system-wide.







Let's Move on to Step 2



1994 (average hydrology) TMDL nitrogen loads.


PerCent change in nitrogen loads.






1994 (average hydrology) TMDL phosphorus loads.


PerCent change in phosphorus loads.








1994 (average hydrology) TMDL solids loads.


PerCent change in solids loads.






























































Net Source or Sink?


- We have three runs:
 - 1. 2010 Progress Run
 - 2. 2010 Progress Run with no Conowingo Reservoir
 - 3. 2010 Progress Run with Step 2 erosion
- If we take 3 minus 2, we get settling (negative) or scour (positive). We can also run a total to get accumulation (negative) or erosion (positive).




Daily Nitrogen Erosion/Settling









Daily Phosphorus Erosion/Settling








Daily Solids Erosion/Settling

Cumulative Solids Erosion



Net Source or Sink?

- We are overestimating the net erosion of TSS and P in our Step 2 runs and/or
- We are overestimating the frequency of scour events.
 - Possibly our threshold for erosion is too low.
 - The bed should armor during scour events.
 - Or we could have a greater settling velocity of solids in the reservoir.
 - The reservoir should fill back in following a major scour event.
- We really need a mass balance in the bed of the Conowingo Reservoir.

I'm Puzzled

- I really don't know what we expect the future Conowingo Reservoir to look like.
- A system with no settling and constant leakage of suspended material over the dam?
- A system with a frequent string of small erosion events that resembles constant leakage?
- A system with rare, major erosion events followed by periods of infilling?
- >>>>>>

Present Indications

- All runs (constant spillage vs. erosion events) indicate summer-average DO depression 0.1 to 0.2 mg/L below currently-projected TMDL levels.
- All runs indicate summer-average chlorophyll increase 1 ug/L above currently-projected TMDL levels.

Present Indications

- All runs indicate minimal effect on projected SAV coverage.
 - We consider light availability only. Not scour or burial or similar effects.
 - We have not examined a major growing-season storm.
- Effects of spillage events are concentrated in the upper 20 km of the bay .
- Effects of erosion events move much further down the bay and even into the lower Potomac River.